

DECLARATION OF PERFORMANCE

No: FRF B600 + FGT B200

1. Unique identification code of the product type: **FRF B600 + FGT B200**
2. Intended use/es: Communication in domestic and commercial locations
3. Manufacturer: Altaterra Kft. H-9431 Fertőd, Malom köz 1, Hungary
www.altaterra.eu
5. Systems of assessment and verification of constancy of performance (AVCP): System 3
6. European Assessment Document: EAD 220062-00-0401, European Technical Assessment: ETA-19/0179,
Technical Assessment Body: ETA Danmark, Notified body/ies: 1235, 0679, 0757, 0845, 1235*
7. Declared performance:

Essential characteristics	Performance	§	NB*
Reaction to fire	class B-s1, d0	2.2.1	0845
External fire performance	NPD	2.2.2	
Watertightness	class 9A	2.2.3	1235
Resistance to wind load	class C3 **	2.2.4	1235
Resistance to snow load	4 mm / -- / 6.6 mm (33.2) laminated /14,5 mm / 4 mm float	2.2.5	
Impact resistance	class 3	2.2.6	1235
Bonding of cover glass	Not relevant	2.2.7	
Airborne sound insulation	36 (-1,-4) dB	2.2.8	0679
Thermal transmittance	$U_{rc,ref300}$: 0,87 W/(m ² K) $A_{rc,ref300}$: 3,4 m ²	2.2.9	1235
Total solar energy transmittance	0,54	2.2.10	0757
Light transmittance	0,72	2.2.11	0757
Frame factor	0,26	2.2.12	
Air permeability	class 3	2.2.13	1235
NPD: No performance determined			
* Notified body/ies: http://ec.europa.eu/growth/tools-databases/nando/			
** For window width > 1200 mm or window height > 1200 mm: NPD			

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.




Krzysztof Dudek
CEO
Altaterra Kft.

Fertőszentmiklós, Hungary 08. 03. 2023



19

FRF B600 + FGT B200
Communication in domestic and commercial locations

European Assessment
Document:
EAD 220062-00-0401
European Technical Assessment:
ETA-19/0179

Essential characteristics	Performance	§	NB*
Reaction to fire	class B-s1, d0	2.2.1	0845
External fire performance	NPD	2.2.2	
Watertightness	class 9A	2.2.3	1235
Resistance to wind load	class C3 **	2.2.4	1235
Resistance to snow load	4 mm / -- / 6.6 mm (33.2) laminated /14,5 mm / 4 mm float	2.2.5	
Impact resistance	class 3	2.2.6	1235
Bonding of cover glass	Not relevant	2.2.7	
Airborne sound insulation	36 (-1,-4) dB	2.2.8	0679
Thermal transmittance	$U_{rc,ref300}$: 0,87 W/(m ² K) $A_{rc,ref300}$: 3,4 m ²	2.2.9	1235
Total solar energy transmittance	0,54	2.2.10	0757
Light transmittance	0,72	2.2.11	0757
Frame factor	0,26	2.2.12	
Air permeability	class 3	2.2.13	1235

NPD: No performance determined

* Notified body/ies: <http://ec.europa.eu/growth/tools-databases/nando/>

** For window width > 1200 mm or window height > 1200 mm: NPD